

1.3 Megapixel IP Mini-Bullet IR Camera



OVERVIEW

- 1/3" 1.3Megapixel progressive scan CMOS
- H.264+ & H.264 dual-stream encoding
- 30fps@1.3M(1280×960)
- DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC
- Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS
- 2.8mm fixed lens
- 100ft IR Night Vision Range
- IP67 - Weatherproof
- PoE - Power Over Ethernet

IPB-70

Image Sensor: 1/3" 1.3Megapixel progressive CMOS
 Effective Pixels: 1280(H) x960(V)
 RAM/ROM: 256MB/16MB
 Scanning System: Progressive
 Minimum Illumination: 0.5Lux/F2.5(Color), 0Lux/F2.5(IR on)
 S/N Ratio: More than 50dB
 IR Distance: Distance up to 100ft
 IR On/Off Control: Auto/ Manual
 IR LEDs: 18
 Lens Type: Fixed
 Mount Type: Board-in
 Focal Length: 2.8mm
 Max. Aperture: F2.5/F2.5
 Angle of View: H:97.5°/73.5°, V:71°/53°
 Focus Control: Fixed
 Close Focus Distance: N/A
 Pan/Tilt Range: Pan:0° ~360°; Tilt:0° ~90°; Rotation:0° ~360°
 Video Compression: H.264+/H.264
 Streaming Capability: 2 Streams
 Resolution: 1.3M(1280×960)/720P(1280×720)/
 D1(704×576/704×480)/CIF(352×288/352×240)
 Frame Rate: 1.3M (1 ~ 25/30fps) D1/CIF(1 ~ 25/30fps)
 Bit Rate Control: CBR/VBR
 Bit Rate: H264:24K ~ 8192Kbps
 Day/Night: Auto(ICR) / Color / B/W
 BLC Mode: BLC / HLC / DWDR
 White Balance: Auto/Natural/Street Lamp/Outdoor/Manual
 Gain Control: Auto/Manual
 Noise Reduction: 3D DNR
 Motion Detection: Off / On (4 Zone, Rectangle)

Region of Interest: Off / On (4 Zone)
 Electronic Image: Support
 Smart IR: Support
 Digital Zoom: 16x
 Flip: 0° / 90° / 180° / 270°
 Mirror: Off / On
 Privacy Masking: Off / On (4 Area, Rectangle)
 Network Ethernet: RJ-45 (10/100Base-T)
 Protocol: HTTP;HTTPS;TCP;ARP;RTSP;RTP;UDP;SMTP;FTP;
 DHCP;DNS;DDNS;PPPOE;IPv4/v6;QoS;UPnP;NTP;
 Bonjour;802.1x;Multicast;ICMP;IGMP;
 Interoperability: ONVIF, PSIA, CGI
 Streaming Method: Unicast / Multicast
 Max. User Access: 10 Users/20 Users
 Edge Storage: NAS(Network Attached Storage)
 Local PC: for instant recording
 Web Viewer: IE, Chrome, Firefox, Safari
 Management Software: Smart PSS, DSS, Easy4ip
 Smart Phone: iPhone, iPad, Android Phone
 Certifications: CE (EN 60950:2000) UL:UL60950-1
 FCC: FCC Part 15 Subpart B
 Power Supply: DC12V PoE (802.3af)(Class 0)
 Power Consumption: <6.8W
 Operating Conditions: -22° F ~ +140° F / Less than 95% RH
 Storage Conditions: -22° F ~ +140° F / Less than 95% RH
 Ingress Protection: IP67 -Weatherproof
 Casing: Metal+Plastic
 Dimensions: 2.76" x 6.49"

Access Anywhere



**7 YEAR
WARRANTY**

**FREE
LIFETIME
SUPPORT**

1.3 MP IP Bullet Camera

IPB-70

www.ClearViewCCTV.com Phone: 855-248-7888

3050 N Andrews Ave Ext. Pompano Beach, FL 33064