

3.0 Megapixel In/Outdoor 2.7~12mm Motorized Zoom 100ft IR



OVERVIEW

- 3.0 Megapixel 1/3" Progressive scan
- 30fps @ 3MP(2048 x 1536)
- 2.7~12mm lens Zoom by Remote Control
- 100ft IR LEDs range
- H.265 & MJPEG dual-stream encoding
- DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC
- OnVif (2.4)
- IP67 - Weatherproof
- IK10 - Vandalproof
- PoE (802.3af) 5W

IPD-92A

Image Sensor: 1/3" 4.0 Megapixel progressive CMOS
Effective Pixels: 2688(H) x 1520(V)
RAM/ROM: 256MB/16MB
Min Illumination: 0.1Lux/F1.4(Color), 0Lux/F1.4(IR on)
S/N Ratio: More than 50dB
IR Distance: Distance up to 98ft
IR On/Off Control: Auto/ Manual
Lens Type: Motorized(-ZS), Manual(-VFS)
Mount Type: Board-in
Focal Length: 2.7mm~12mm
Max. Aperture: F1.4
Angle of View: H:100°~35°, V:54°~20°
Focus Control: Motorized(-ZS), Manual(-VFS)
Close Focus Distance: 0.3m
Pan/Tilt Range: Pan:0°~355°; Tilt:0°~75°; Rotation:0°~355°
Compression: H.264+/H.264
Streaming Capability: 2 Streams
Resolution: 4M(2688x1520) / 3M(2048x1536) (2304x1296) / 1080P(1920x1080) / 720P(1280x720) / D1(704x576/704x480) / CIF(352x288/352x240)
Frame Rate: 4M(1~20fps) / 2M(1~30fps) D1/CIF(1~30fps)
Bit Rate Control: CBR/VBR
Bit Rate: H264:24K ~ 8192Kbps
Day/Night: Auto(ICR) / Color / B/W
BLC Mode: BLC / HLC / WDR(120dB)
White Balance: Auto / Natural / Street Lamp / Outdoor / Manual
Gain Control: Auto / Manual
Noise Reduction: 3D DNR
Motion Detection: Off / On (4 Zone, Rectangle)

Region of Interest: Off / On (4 Zone)
Smart IR: Support
Digital Zoom: 16x
Flip: 0° / 90° / 180° / 270°
Mirror: Off / On
Privacy Masking: Off / On (4 Area, Rectangle)
Ethernet: RJ-45 (10/100Base-T)
Protocol: HTTP, HTTPS, TCP, ARP, RTSP, RTP, UDP, SMTP, FTP, DHCP, DNS, DDNS, PPPoE, IPv4/v6, QoS, UPnP, NTP, Bonjour, 802.1x, Multicast, ICMP, IGMP, Interoperability ONVIF, PSIA, CGI
Streaming Method: Unicast / Multicast
Edge Storage: NAS(Network Attached Storage)
Local PC for instant recording
Micro SD Card 128GB
Web Viewer: IE, Chrome, Firefox, Safari
Management Software Smart PSS, DSS, Easy4ip
Smart Phone: IOS, Android
Certifications: CE (EN 60950:2000) UL:UL60950-1
FCC: FCC Part 15 Subpart B
Power Supply: DC12V PoE (802.3af)(Class 0)
Power Consumption: <9.75W
Operating Conditions: -22° F ~ +140° F / Less than 95% RH
Storage Conditions: -22° F ~ +140° F / Less than 95% RH
Ingress Protection: IP67
Vandal Resistance: IK10
Casing: Metal
Dimensions: 4.80x3.50"
Net Weight: 0.88lb **Gross Weight:** 1.19lb

Access Anywhere

Android

iPhone

Most OS



7 YEAR WARRANTY

FREE LIFETIME SUPPORT

3.0 MP IP Dome Camera

IPD-92A

www.ClearViewCCTV.com Phone: 855-248-7888

3050 N Andrews Ave Ext. Pompano Beach, FL 33064