

4.0 Megapixel IP WDR IR Mini Dome Camera



OVERVIEW


- 1/3" 4.0 Megapixel progressive scan CMOS
- H.265+ & H.264+ dual-stream encoding
- 30fps@4MP(2688x1520)
- WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC
- Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS
- 2.7mm ~ 12mm motorized lens
- 165ft IR Range
- Micro SD memory
- IP67 - Weatherproof
- IK10 - Vandalproof
- PoE - Power Over Ethernet

IPD-93A

Image Sensor: 1/3" 4Megapixel progressive scan CMOS
 Effective Pixels: 2688(H)x1520(V)
 RAM/ROM: 512MB/32MB
 Scanning System: Progressive
 Minimum Illumination: 0.03Lux/F1.4 (Color); 0Lux/F1.4 (IR on)
 S/N Ratio: More than 50dB
 IR Distance: Distance up to 50m (165ft) with 3 LEDs
 IR On/Off Control: Auto/ Manual
 Lens Type: Motorized/ Auto Iris(DC)
 Mount Type: Board-in
 Focal Length: 2.7mm~12mm
 Max. Aperture: F1.4
 Angle of View: H: 100°~35° , V:54°~20°
 Optical Zoom: 4x
 Focus Control: Motorized, Close Focus Distance: 0.3m
 Pan/Tilt/Rotation: Pan0°~355°; Tilt0°~65°; Rotation:0°~355°
 Intelligence: IVS (optional) Tripwire, Intrusion, Object Abandoned/Missing
 Advanced Intelligent Functions: Face Detection
 Video Compression: H.265+/H.265/H.264+/H.264
 Streaming Capability: 3 Streams
 Resolution: 4M(2688x1520) / 3M(2304x1296) / 1080P(1920x1080) / 1.3M(1280x960) / 720P(1280x720) / D1(704x480) / VGA(640x480) / CIF(352x240)
 Main Stream: 4M(1~25/30fps)
 Sub Stream: D1(1~25/30fps)
 Third Stream: 720P(1~25/30fps)
 Bit Rate Control: CBR/VBR
 Bit Rate: H.264: 24~1024Kbps H.265: 14~9984Kbps
 Day/Night: Auto(ICR) / Color / B/W
 BLC Mode: BLC / HLC / WDR(120dB)
 White Balance: Auto/Natural/Street Lamp/Outdoor/Manual
 Gain Control: Auto/Manual
 Noise Reduction: 3D DNR

Motion Detetion: Off / On (4 Zone, Rectangle)
 Region of Interest: Off / On (4 Zone)
 Smart IR: Support
 Digital Zoom: 16x
 Flip: 0° / 90° / 180° / 270°
 Mirror: Off / On
 Privacy Masking: Off / On (4 Area, Rectangle)
 Audio Compression: G.711a/ G.711Mu/ AAC/ G.726
 Network Ethernet: RJ-45 (10/100Base-T)
 Protocol: HTTP; HTTPS; TCP; ARP; RTSP; RTP; UDP; SMTP; FTP; DHCP; DNS; DDNS; PPPoE; IPv4/v6; QoS; UPnP; NTP; Bonjour; 802.1x; Multicast; ICMP; IGMP; SNMP
 Interoperability: ONVIF, PSIA, CGI
 Streaming Method: Unicast / Multicast
 Max. User Access: 10 Users / 20 Users
 Edge Storage: NAS
 Local PC for instant recording: Micro SD card 128GB
 Web Viewer: IE, Chrome, Firefox, Safari
 Management Software: Smart PSS, DSS, Easy4ip
 Smart Phone: IOS, Android
 Certifications: CE (EN 60950:2000) UL:UL60950-1 FCC:FCC Part 15 Subpart B
 Audio Interface: 1/1 channel In/Out
 Alarm: 1/1 channel In/Out
 Power Supply: DC12V, AC24V, PoE(802.3af)(Class 0)
 Power Consumption: <12.5W
 Operating Conditions: -22° F ~ +140° F / Less than 95% RH
 Ingress Protection: IP67 - Weatherproof
 Vandal Resistance: IK10
 Casing: Metal Dimensions: 6.26" x 4.64"
 Net Weight: 0.89kg (1.96lb)

Access Anywhere



4.0 MP IP Dome Camera

IPD-93A

www.ClearViewCCTV.com Phone: 855-248-7888

3050 N Andrews Ave Ext. Pompano Beach, FL 33064