

PantherView HD-AVS DVR Kit 8 Channel 8 Bullet 720p Cameras



PantherView08-8B-720-Kit

Main Processor: Embedded Linux processor Video Input: 8 channel BNC HD-AVS: 1080P/720P HDCVI Camera **IP:** Support 2ch 1080P/720P IP Camera Display Interface: 1 HDMI, 1 VGA **Resolution:** 1920×1080, 1280×1024, 1280×720, 1024×768 Display Split: 1/4/8/9 **Privacy Masking:** 4 rectangular zones (each camera) OSD: Title, Time, Video loss, lock, Motion detection, Recording Recording Video/Audio Compression: H.264/G.711 Main Stream: 1080P(1~15fps)/720P/960H/D1 (1~25/30fps) Extra Stream: CIF/QCIF(1~25/30fps), D1 Bit Rate: 96~4096Kb/s **Record Mode:** Manual, Schedule(Continuous, MD), Stop Record Interval: 1~60 min, Pre: 1~30 sec, Post: 10~300 sec Trigger Events: Recording, PTZ, Tour, Alarm out, Video Push, Email, FTP, Snapshot, Buzzer & Screen tips Video Detection: Motion Detection, MD Zones: 396(22×18), Video Loss & Camera Blank Alarm Input: 8 channel Relay Output: 3 channel

OVERVIEW

- 8 Channel 1080P HD Recording
- Tribrid Works with HD-AVS, 2 Ch IP & Analog
- 8 HD1-BL21 720P HD-AVS Cameras
- H.264 dual-stream video compression
- HDMI / VGA simultaneous video output
- Synchronous realtime playback, GRID interface & smart search
- 3D intelligent positioning with our PTZ cameras
- Support 1 SATA HD up to 6TB, 2 USB2.0
- Includes 1,000 GB Drive, Mouse

Audio Input: 4 channel, RCA Audio Output: 1 channel, RCA Two-way Talk: Reuse audio input/output channel 1 Sync Playback: 1/4/9 **Search Mode:** Time/Date, MD & Exact search (to second) Playback Functions: Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom Backup Mode: USB Device/Internal SATA burner/Network Ethernet: RJ-45 port (10/100M) Network Functions: HTTP, IPv4/IPv6, TCP/IP, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, SNMP, P2P Max. User Access: 128 users Internal HDD: 2 SATA ports, up to 8TB USB Interface: 2 ports(1 Rear), USB2.0 RS485: 1 port, For PTZ control Power Supply: DC12V/4A, 15W Working Environment: -10°C ~+55°C / 10%~90%RH Dimension: 14.76"×11.22"×2.16" Access Anywhere Weight: 5.18 lbs (without HDD) בוסדכחה 🌔

[] iPhone



3050 N Andrews Ave Ext. Pompano Beach, FL 33064

WARRANI